


宽体扁平卸扣

- 比传统结构卸扣截面更大，受力更好
- 55t~300t 最大试验载荷为额定工作载荷的 2 倍
- 400t 最大试验载荷为额定工作载荷的 1.5 倍
- 500t~1000t 最大试验载荷为额定工作载荷的 1.33 倍
- 最小破断载荷均为额定工作载荷的 4 倍
- 选用优质合金钢经淬火和回火处理，强度更高
- 卸扣本体采用自由锻工艺
- 螺母分圆形和六角形两种
- 卸扣本体上有额定工作载荷标识
- 用于连接高强度吊带、钢丝绳索具等，因截面大，钢丝绳索具的耐磨性能可明显提高
- 卸扣表面镀锌处理
- 可接受特殊尺寸定制



产品型号	额定载荷 (t)	尺寸 (mm)						自重 kg/只
		W	D	P	A	O	S	
BK55	55	85	57	100	55	160	240	33
BK85	85	110	76	130	75	200	310	79
BK120	120	130	85	150	85	220	365	111
BK150	150	140	95	170	90	250	390	155
BK200	200	150	105	205	100	280	460	252
BK300	300	185	134	265	120	350	630	452
BK400	400	220	160	320	145	370	650	759
BK500	500	250	180	340	160	450	700	1092
BK600	600	275	200	370	170	490	760	1405
BK700	700	300	215	400	190	540	780	1704
BK800	800	325	230	420	200	554	850	1959
BK900	900	350	255	440	220	584	900	2450
BK1000	1000	380	270	460	240	614	900	2567

