



Eye-Eye webbing sling

- According to JB/T8521.1.2007 and EU EN1492-1:2000+A1:2008 standard.
- The webbing sling of polyamide, polyester and polypropylene can be provided according to different service environments.
- Suitable temperature: polyester, polyamide $-40^{\circ}\text{C}\sim 100^{\circ}\text{C}$, polypropylene $-40^{\circ}\text{C}\sim 80^{\circ}\text{C}$.
- Wear-resistant sheath sewn on the ring.
- Safety factor 6:1 or 7:1



TYPE W01 Standard Type									
Model	Color	WLL (kg)	Thickness (mm)	Width 6:1 (mm)	Width 7:1 (mm)	Length (m)	Eye length (mm)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
W01-01		1000	7.5	25	30	1.1~100	350	0.2	0.26
W01-02		2000	7.5	50	60	1.2~100	400	0.41	0.45
W01-03		3000	7.5	75	90	1.3~100	450	0.6	0.71
W01-04		4000	7.5	100	120	1.4~100	500	0.75	1.02
W01-05		5000	7.5	125	150	2.0~100	550	1.02	1.21
W01-06		6000	7.5	150	180	2.0~100	600	1.26	1.42
W01-08		8000	7.5	200	240	2.0~100	700	1.69	1.89
W01-10		10000	7.5	250	300	3.0~100	800	2.07	2.34
W01-12		12000	7.5	300	300	3.0~100	900	2.37	2.98
TYPE W02 Thickening Type									
Model	Color	WLL (kg)	Thickness (mm)	Width 6:1 (mm)	Width 7:1 (mm)	Length (m)	Eye length (mm)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
W02-02		2000	15	25	30	1.5~100	350	0.45	0.53
W02-04		4000	15	50	60	1.5~100	400	0.85	0.93
W02-06		6000	15	75	90	1.5~100	450	1.34	1.45
W02-08		8000	15	100	120	2.0~100	500	1.79	2.05
W02-10		10000	15	125	150	2.0~100	550	2.26	2.66
W02-12		12000	15	150	180	3.0~100	600	2.72	2.96
W02-16		16000	15	200	240	3.0~100	700	3.68	3.82
W02-20		20000	15	250	300	3.0~100	800	4.73	4.96
W02-24		24000	15	300	300	3.0~100	900	5.21	5.59

W02-30		30000	20	300	300	3.5~100	1000	6.95	7.45
TYPE W05 Widening Type									
Model	Color	WLL (kg)	Thickness (mm)	Width 6:1 (mm)	Width 7:1 (mm)	Length (m)	Eye length (mm)	Weight 6:1 (kg/m)	Weight 7:1 (kg/m)
W05-01		1000	5	50	60	1.2~100	350	0.2	0.26
W05-02		2000	5	100	120	1.3~100	400	0.41	0.45
W05-03		3000	5	150	180	1.4~100	450	0.6	0.71
W05-04		4000	5	200	240	1.8~100	500	0.75	1.02
W05-05		5000	5	250	300	2.0~100	550	1.02	1.21
W05-06		6000	5	300	300	2.3~100	600	1.26	1.42
W05-08		8000	8	200	240	2.3~100	450	1.69	1.89
W05-10		10000	8	250	300	2.3~100	500	2.07	2.34
W05-12		12000	8	300	360	2.4~100	550	2.37	2.98
W05-16		16000	8	400	480	2.5~100	600	3.68	3.82
W05-20		20000	8	500	600	2.6~100	650	4.73	4.96
W05-24		24000	8	600	600	2.8~100	700	5.21	5.59
W05-30		30000	10	600	600	3.0~100	750	6.95	7.45

