

Ratchet Tensioner

- According to EN12195-3.
- Die forging technology, surface finish: power plastified.
- Customizing the length of the chain according to the customer's requirements



ITEM No.	WLL	Breaking Load	Size (mm)						Weight
	KN		KN	A	B	H	Lmin	Lmax	
LSJG-8	40	80.4	50	25	92	340	500	210	3.18
LSJG-10	63	126	50	25	118	365	525	280	5.3
LSJG-13	100	212	72	30	146.5	365	525	355	8.4
LSJG-16	160	322	72	32	178	390	550	355	8.8

Lashing Chains

- According to EN818-4、GB/T20652
- It has the advantages of wear resistance, high temperature resistance, corrosion resistance, low ductility and no elongation after force.
- Customizing the length of the chain according to the customer's requirements.
- It can be used with the ratchet tensioner.



ITEM No.	Diameter(mm)	Length(m)	WLL (kg)	Breaking Load (kg)	Chain Weight(kg)	safety factor
LS2G-6	6	8	1120	4480	7	4:1
LS2G -8	8	8	2000	8000	12	4:1
LS2G -10	10	8	3200	12800	19.7	4:1
LS2G -13	13	8	5300	21200	34.4	4:1
LS2G -16	16	8	8000	32000	52.5	4:1