

### Wire Rope Braiding Belt Sling

- Longer life and higher strength than traditional wire rope
- It is more wear-resistant and cutting-resistant than polyester lifting belt.
- Working Load, eye length, width and length can be customized according to customers.



ITEM No.	WLL	Width	Thickness	Eye length	Weight/M	Weight / increase per metre
GSBD-0.75	0.75	30	6	195	1.6	1
GSBD-1.25	1.25	40	6	195	1.9	1.3
GSBD-2	2	40	10	300	4.1	2.2
GSBD-3	3	60	10	300	4.5	2.5
GSBD-6	6	90	10	400	7.2	4.6
GSBD-8	8	120	10	400	9.2	6.2

### Wire Rope Braiding Belt Sling (Nine strand)

- Processing range: 40mm~320mm.
- This braiding structure increases the working load. .
- Under the same tonnage condition, the self-weight is reduced and the length can be shorter.
- Special treatment of ring eye part, prolongs the service life.



ITEM No.	Diameter(wire rope)	Diameter(product)	Eye Size	WLL	Breaking Strength
	mm			KN	
JGGS-40	10	40	350	84	420
JGGS-44	11	44	385	101	505
JGGS-48	12	48	420	121	605
JGGS-52	13	52	455	142	710
JGGS-56	14	56	490	165	825
JGGS-64	16	64	560	215	1075
JGGS-72	18	72	630	272	1360
JGGS-80	20	80	700	337	1685
JGGS-88	22	88	770	407	2035
JGGS-96	24	96	840	484	2420
JGGS-104	26	104	910	569	2845
JGGS-112	28	112	980	660	3300

JGGS-128	32	128	1120	862	4310
JGGS-144	36	144	1260	1091	5455
JGGS-160	40	160	1400	1347	6735
JGGS-176	44	176	1540	1629	8145
JGGS-192	48	192	1680	1932	9660
JGGS-208	52	208	1820	2274	11370
JGGS-224	56	224	1960	2633	13165
JGGS-240	60	240	2100	3026	15130
JGGS-256	64	256	2240	3437	17185
JGGS-264	66	264	2310	3659	18295
JGGS-272	68	272	2380	3314	16570
JGGS-280	70	280	2450	3512	17560
JGGS-288	72	288	2520	3716	18580
JGGS-296	74	296	2590	3924	19620
JGGS-304	76	304	2660	4140	20700
JGGS-312	78	312	2730	4360	21800
JGGS-320	80	320	2800	4588	22940